

1 GHz SPLITTERS

5-1000MHz

FEATURES :

- Frequency range : 5-1000 MHz
- Zinc die cast housing
- Grounding terminal provided.
- Low insertion loss, high return loss



Model : SPL - 3772 , 2 WAYS CATV SPLITTER

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Insertion Loss (dB)	≤3.7	≤3.7	≤4.2	≤4.2
Isolation (dB)	≥30	≥25	≥25	≥25
Return Loss (dB)	≥16	≥18	≥18	≥16



Model : SPL - 3773 , 3 WAYS CATV SPLITTER

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Insertion Loss (dB)	≤6.2	≤6.4	≤6.5	≤6.5
Isolation (dB)	≥25	≥22	≥22	≥22
Return Loss (dB)	≥16	≥18	≥18	≥16



Model : SPL - 3774 , 4 WAYS CATV SPLITTER

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Insertion Loss (dB)	≤7.5	≤7.9	≤7.9	≤8.0
Isolation (dB)	≥25	≥24	≥24	≥22
Return Loss (dB)	≥16	≥18	≥18	≥16



Model : SPL - 3776 , 6 WAYS CATV SPLITTER

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Insertion Loss (dB)	≤9.2	≤9.5	≤10.2	≤11.5
Isolation (dB)	≥25	≥25	≥25	≥22
Return Loss (dB)	≥16	≥18	≥18	≥16



Model : SPL - 3778 , 8 WAYS CATV SPLITTER

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Insertion Loss (dB)	≤10.8	≤11.5	≤11.5	≤12.0
Isolation (dB)	≥25	≥25	≥25	≥23
Return Loss (dB)	≥16	≥18	≥18	≥16