

เครื่องสำรองไฟฟ้า

CLEANLINE[®]

UPS



True On-Line Double Conversion Design

Tower and 19" Rack-mount Model

T-1000, TR-1000:	1kVA/900W
T-1500, TR-1500:	1.5kVA/1,350W
T-2000, TR-2000:	2kVA/1,800W
T-3000, TR-3000:	3kVA/2,700W



KEY Features:

- True on-line double conversion design UPS
- 100% digitized microprocessor controlled
- Output power factor 0.9
- Wide input voltage range 110-300Vac
- 50/60 Hz frequency converter mode
- MIMIC LCD for real-time UPS status display
- Auto self-testing system while turning on UPS
- ECO mode operation for energy saving
- Emergency power off (EPO) function
- Programmable power management outlets
- Selectable output voltage via LCD panel
- Cold start function
- Smart battery charger design to optimize battery performance
- Battery charger with temperature compensation technology
- Short circuit protection
- Lightning and surge protection
- Built-in USB and RS-232 communications port for management software
- Generator compatible
- **Optional external Battery for Expansion back up time and Hot Swappable Battery**
- **Optional external maintenance bypass switch**
- **Optional compatible with SNMP protocol**
- **UPS Monitoring and Controlling Software, Available for immediate download via the website**