

SAT Splitter (5-2400MHz)



4202APN

Features:

- + Zinc die-cast housing, nickel-plated
- + Easy installation with two edge hole sites
- + Frequency Range: 5-2400 MHz
- + Power passing-24V 0.8A (MAX.)
- + Indoor using
- + All ports F-(f) connector, 75Ohm
- + Screening factor: 40-450MHz \geq 75dB , 450-860MHz \geq 65dB , 860-2400MHz \geq 55dB

Specifications : 4202APN

Frequency Range (MHz)	Insertion Loss(dB)	Mutual Isolation(dB)	Return Loss(dB)
5-40	\leq 4.0	\geq 18	\geq 10
40-1000	\leq 4.5	\geq 22	\geq 12
1000-1750	\leq 5.0	\geq 22	\geq 12
1750-2400	\leq 5.5	\geq 20	\geq 10



4203APN

Specifications : 4203APN

Frequency Range (MHz)	Insertion Loss(dB)	Mutual Isolation(dB)	Return Loss(dB)
5-40	\leq 7.5	\geq 22	\geq 10
40-1000	\leq 8.0	\geq 25	\geq 12
1000-1750	\leq 9.5	\geq 22	\geq 12
1750-2400	\leq 10.5	\geq 20	\geq 10



4204APN

Specifications : 4204APN

Frequency Range (MHz)	Insertion Loss(dB)	Mutual Isolation(dB)	Return Loss(dB)
5-40	\leq 8.0	\geq 22	\geq 10
40-1000	\leq 8.5	\geq 25	\geq 12
1000-1750	\leq 9.5	\geq 22	\geq 12
1750-2400	\leq 11.0	\geq 20	\geq 10



4206APN

Specifications : 4206APN

Frequency Range (MHz)	Insertion Loss(dB)	Mutual Isolation(dB)	Return Loss(dB)
5-40	\leq 10.5	\geq 22	\geq 10
40-1000	\leq 11.0	\geq 25	\geq 12
1000-1750	\leq 12.5	\geq 22	\geq 12
1750-2400	\leq 15.5	\geq 20	\geq 10



4208APN

Specifications : 4208APN

Frequency Range (MHz)	Insertion Loss(dB)	Mutual Isolation(dB)	Return Loss(dB)
5-40	\leq 12.0	\geq 22	\geq 10
40-1000	\leq 12.0	\geq 25	\geq 12
1000-1750	\leq 14.5	\geq 22	\geq 12
1750-2400	\leq 16.0	\geq 20	\geq 10