

- ◆ 19" PREMIUM EXPORT RACK design & produce under ANSI/EIA-310D – 1992 (Rev.EIA-310-C), IEC60297-1, IEC 60927-2, BS 5954 : Part2, DIN 41494 standard
- ◆ Modular knock down system for easily transport & assembly
- ◆ Produced from Electro-Galvanized Steel Sheet. Prevents rust 100%
  - Front – Rear, Side cover material thickness 1.5mm.
  - Mounting Angle Pole , Frame structure, Bottom Base material thickness 2.0mm.
  - Support base for Caster material thickness 3.0mm.
- ◆ Special design 4 Mounting Angle Pole in C-shape for increasing strength for heavy equipment with square mounting hole size 9.5x9.5mm.
- ◆ Adjustable Mounting Pole position with U screen for easily installation.
- ◆ Front door panel is perforated attached with premium grade Acrylic thickness 5mm.
- ◆ Gray rubber also attached for each door to protect dust. The front door is security locks by swing handle with master key system.
- ◆ Rear door is full perforated panel. Gray rubber also attached for each door to protect dust. The rear door come with security camlock with master key system.
- ◆ 3 Premium grade PVC Hinges for each door were attached with easily open and close. The frame structure also provided the common hole for any users for easily swap the direction when open-close the door by themselves.
- ◆ Side Panels come together with 2 Premium grade slide latches per panel and security cam lock with master key system
- ◆ Roof Cover also designed for installing up to 6 ventilating fan which compatible with 1x 4" , 2x4" , 3x4" fan set
- ◆ Bottom Base also designed for heavy load with soft slide shutter function for all cables. Soft slide shutter also come with the soft gray sponge to protect insect and small animals to enter the rack from bottom.
- ◆ Adjustable levelling feet for aligns on uneven surface also cover with ABS material in order to protect Electrostatic and ground reason.
- ◆ Caster is Nylon six and 360 degree swivel plate which can be easily moving. Each caster can pass static load of 150 kg./caster.
- ◆ Rack Color is New Shine Two-Tone (Light Gray-Dark Gray) which using Electro static Powder Coating system
- ◆ For Grounding system also installing 2 ground cable size 2.5mm (Yellow-green color) length 18cm.connect the frame with front and rear door.
- ◆ For side panels also intall 4 ground cable (Yellow-green color) length 13cm.
- ◆ Rack has static load capacity 1,400 kgs. (pass the weight test and certificate by KMUTT).
- ◆ 19" Premium Export Rack are manufactured under ISO9001 : 2015 and ISO 14001 system.



| 19" PREMIUM EXPORT SERVER RACK |        |          |          |          |          |          |          |
|--------------------------------|--------|----------|----------|----------|----------|----------|----------|
|                                | U      | 15U      | 27U      | 36U      | 39U      | 42U      | 45U      |
| W=60cm                         | Height | 85cm     | 139cm    | 179cm    | 185cm    | 205cm    | 218.5cm  |
|                                | Depth  | 60cm     | 60cm     | 60cm     | 60cm     | 60cm     | 60cm     |
|                                |        | S4-60615 | S4-60627 | S4-60636 | S4-60639 | S4-60642 | S4-60645 |
|                                |        | S4-60815 | S4-60827 | S4-60836 | S4-60839 | S4-60842 | S4-60845 |
|                                |        | S4-60915 | S4-60927 | S4-60936 | S4-60939 | S4-60942 | S4-60945 |
|                                |        | S4-61015 | S4-61027 | S4-61036 | S4-61039 | S4-61042 | S4-61045 |
| W=80cm                         | Height | 85cm     | 139cm    | 179cm    | 185cm    | 205cm    | 218.5cm  |
|                                | Depth  | 80cm     | 80cm     | 80cm     | 80cm     | 80cm     | 80cm     |
|                                |        | S4-80815 | S4-80827 | S4-80836 | S4-80839 | S4-80842 | S4-80845 |
|                                |        | S4-80915 | S4-80927 | S4-80936 | S4-80939 | S4-80942 | S4-80945 |
|                                |        | S4-81015 | S4-81027 | S4-81036 | S4-81039 | S4-81042 | S4-81045 |
|                                |        | S4-81115 | S4-81127 | S4-81136 | S4-81139 | S4-81142 | S4-81145 |