

WALL RACK OUTDOOR



Push Handle Lock



Rubber Seal



Mounting Pole
w/Screen UH



Mounting Pole
Can be Adjusted



3 Knock Out Holes



Grounding



FEATURES

- **Designed** to comply with the standard of ANSI/EIA - 310D - 1992 (Rev.EIA- 310C).
- **19" Wall Rack type** for outdoor, suitable for Network Equipment 19" standard or FDU, Patch Panel and suitable for CCTV system.
- **Designed with a height** of 6U, 9U or 12U.
- **The cabinet compliant** with IP54 (Dust and Water protection).
- **Designed of two layer**, The front and side panel have a sun shield layer for outdoor Harsh Environment installation.
- **Structure** Produced from Electro - Galvanized steel sheet with thickness of 1.2 mm., Light weight and completed rust proof.
- **Front door** Designed of two layers, provide build in Handle Lock. Ventilation by roofer at front door. Open through 120 degrees.
- **Side Panel (two doors)** Designed of two layers with two security lock for safety. Water proof, dust filter and ventilation by roofer at side panel open through 120 degrees.
- **Back Side** Supporting by four Steel support bar with thickness of 2.0mm.
- **Roof cover** The top can be mounted with 1 to 3 of 4" ventilating fans to release the accumulated heat inside the cabinet and extend the life of equipment., On the roof cover has the ventilation grill.
- **Front door, Side panel and Roof cover** are water proof by Polyurethane gasket (UL Listed) without cutting Joint IP55.
- **Mounting pole** Produced from Electro - Galvanized steel with thickness of 2.0 mm. They can be adjusted in/out (8 level) to meet customer's need Provide the U-height screened on the mounting pole.
- **Base** Provide removable plate with rubber shield., Provide 3 knock out holes size 3/4" and 1" for cable entry.
- **Grounding** Provide 3 ground wires connecting between structure and doors.
- **Color** The Special dark gray outdoor colour by electrostatic powder coating, Scratch resistance and rust protection.
- **Manufacturing and Distribution** Compliant with ISO 9001:2015 and ISO 14001:2015

ORDERING INFORMATION

Order No.	Description (size)	Color
S1-60406OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 6U D 40 cm. (w60xd50xh48 cm.)	Dark Grey
S1-60409OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 9U D 40 cm. (w60xd50xh61.5 cm.)	Dark Grey
S1-60412OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 12U D 40 cm. (w60xd50xh75 cm.)	Dark Grey
S1-60506OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 6U D 50 cm. (w60xd60xh48 cm.)	Dark Grey
S1-60509OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 9U D 50 cm. (w60xd60xh61.5 cm.)	Dark Grey
S1-60512OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 12U D 50 cm. (w60xd60xh75 cm.)	Dark Grey
S1-60606OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 6U D 60 cm. (w60xd70xh48 cm.)	Dark Grey
S1-60609OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 9U D 60 cm. (w60xd70xh61.5 cm.)	Dark Grey
S1-60612OUT	19" PREMIUM EXPORT WALL RACK OUTDOOR, 12U D 60 cm. (w60xd70xh75 cm.)	Dark Grey

RECOMMEND ACCESSORIES

Order No.	Description	Color
S7-05001	1 x 4" Heavy Duty Fan	Black
S7-05002	2 x 4" Heavy Duty Fan	Black, Light Grey
S7-00006	AC Power Distribution 6 Outlet w/Cable 3M & Surge Protection	Light Grey